DISTRIBUTION

## SECRET

OUT64032

19 17**Z** 1968 JAN 10

P 101906Z JAN 68 FM NPIC WASHDC TO RUCSAAA/SAC OFFUTT AFB CMAHA NEB RUCVAAA/4080 STRAT WG OL 19 BARKSDALE AFB LA RUCVAAA/2D RTS BAPKSDALE AFB LA PUEPJS/DIA WASHDC PUCIJRA/NAVPECONTECHSUPPCEN SUITLAND MD EUWBKNA/15TH AF MARCH AFB RIVERSIDE CALIF RUCVAAA/2 AF BARKSDALE AFB LA PUEFHQA/HOS USAF/AFRDR INFO PUEPIA/CIA WASHDC RT SECPET CITE NPIC 2689. 15TH AF (FOR DI), SAC (GLASS LAMP/DOCR, DM 4) 2D AF (FOR DI). 1. CAMERA B-24 WAS USED ON MISSION G-005 FLOWN 5 JANUARY AFRDE L. 1968. PROCESSING WAS ACCOMPLISHED BY NAV RECON TECH SUPPCEN.

Office File Cable Sac. Ex Staff Secur 155 PS PPS 143 DIAXX-4 SPAD 25) DIA Advance copy Sunitized

Action

2. ORIGINAL NEGATIVE:

A. DEMSITY AND RESOLUTION ARE GOOD.

9F SIDE: FOG IS PRESENT INTERMITTENTLY ON THE OUTBOARD EDGE. MINUS DENSITY DOTS ARE PRESENT IN THE FIRST 22 FRAMES SPACED 2.3 INCHES APART AND Ø.4 INCH IN FROM THE INBOARD EDGE. FRAMES 301 TO 600 CONTAIN FOGGED AREAS INTERMITTENTLY ALONG THE MAJOR AXIS OF THE FILM ONE TO TWO INCHES IN FROM THE INBOARD EDGE. A HEAT SPLICE IS PRESENT BETWEEN FRAMES 691 AND 692.

9L SIDE: MINUS DENSITY DOTS ARE PRESENT IN THE FIRST 99 FRAMES, 1.7 INCHES APART AND 1.5 INCHES FROM THE OUTBOARD EDGE. MINUS DENSITY DOTS ARE ALSO PRESENT IN THE FIRST 300 FRAMES 1.7 INCHES APART AND PROGRESSING FROM 0.4 INCH TO 1.0 INCH IN FROM THE INPOARD EDGE. FRAME 666 CONTAINS A HEAT SPLICE.

D. BOTH SIDES: MODE V OF CAMERA OPERATION WAS UTILIZED

THROUGHOUT; HOWEVER, FRAME 1282 IS A 3P. THE LAST TITLED FRAME IS 1284.

3. POSITIVES:

A. PI SUITABILITY IS GOOD.

B. PRINTING AND PROCESSING ARE GOOD.

C. CLOUDS OBSCUPE APPROXIMATELY 40 PERCENT OF THE MISSION.

GP - 1

SECPET

END OF MESSAGE

SECRET

Excluded from automatic downerading and declassification